

Title

markerlabelstyle — Choices for overall look of marker labels

[Description](#)[Syntax](#)[Remarks and examples](#)[Also see](#)

Description

markerlabelstyle defines the position, gap, angle, size, and color of the marker label. See [G-3] [marker_label_options](#) for more information.

markerlabelstyle is specified in the `mllabstyle()` option,

```
. graph ..., mllabstyle(markerlabelstyle) ...
```

Sometimes (for example, with `twoway scatter`), a *markerlabelstylelist* is allowed: a *markerlabelstylelist* is a sequence of *markerlabelstyles* separated by spaces. Shorthands are allowed to make specifying the list easier; see [G-4] [stylelists](#).

Syntax

<i>markerlabelstyle</i>	Description
p1–p15	used by first to fifteenth plot
p1box–p15box	used by first to fifteenth “box” plot

Other *markerlabelstyles* may be available; type

```
. graph query markerlabelstyle
```

to obtain the complete list of *markerlabelstyles* installed on your computer.

Remarks and examples

stata.com

Remarks are presented under the following headings:

What is a markerlabel?

What is a markerlabelstyle?

You do not need to specify a markerlabelstyle

Specifying a markerlabelstyle can be convenient

What are numbered styles?

What is a markerlabel?

A marker label is identifying text that appears next to (or in place of) a marker. Markers are the ink used to mark where points are on a plot.

What is a *markerlabelstyle*?

The look of marker labels is defined by five attributes:

1. the marker label's position—where the marker is located relative to the point; see [G-4] *clockposstyle*
2. the gap between the marker label and the point; see [G-4] *clockposstyle*
3. the angle at which the identifying text is presented; see [G-4] *anglestyle*
4. the overall style of the text; see [G-4] *textstyle*
 - a. the size of the text; see [G-4] *textsizestyle*
 - b. the color and opacity of the text; see [G-4] *colorstyle*
5. the format of text, which is useful when labels are numeric; see [D] **format**

The *markerlabelstyle* specifies all five of these attributes.

You do not need to specify a *markerlabelstyle*

The *markerlabelstyle* is specified by the option

```
mstyle(markerlabelstyle)
```

Correspondingly, you will find other options available:

```
mlabposition(clockposstyle)
```

```
mlabgap(size)
```

```
mlabangle(anglestyle)
```

```
mlabtextstyle(textstyle)
```

```
mlabsize(textstyle)
```

```
mlabcolor(colorstyle)
```

```
mlabformat(%fmt)
```

You specify the *markerlabelstyle* when a style exists that is exactly what you want or when another style would allow you to specify fewer changes to obtain what you want.

Specifying a *markerlabelstyle* can be convenient

Consider the command

```
. scatter y1 y2 x, mlabel(country country)
```

Assume that you want the marker labels for *y2* versus *x* to appear the same as for *y1* versus *x*. (An example of this can be found under *Eliminating overprinting and overruns* and under *Advanced use* in [G-3] *marker_label_options*.) You might set all the attributes for the marker labels for *y1* versus *x* and then set all the attributes for *y2* versus *x* to be the same. It would be easier, however, to type

```
. scatter y1 y2 x, mlabel(country country) mlabstyle(p1 p1)
```

When you do not specify `mlabstyle()`, results are the same as if you specified

```
mlabstyle(p1 p2 p3 p4 p5 p6 p7 p8 p9 p10 p11 p12 p13 p14 p15)
```

where the extra elements are ignored. In any case, *p1* is one set of marker-label attributes, *p2* is another set, and so on.

Say that you wanted y_2 versus x to look like y_1 versus x , except that you wanted the line to be green; you could type

```
. scatter y1 y2 x, mlabel(country country) mlabstyle(p1 p1)
      mlabcolor(. green)
```

There is nothing special about *markerlabelstyle* p_1, p_2, \dots ; they merely specify sets of marker-label attributes, just like any other named *markerlabelstyle*. Type

```
. graph query markerlabelstyle
```

to find out what other marker-label styles are available.

Also see [Appendix: Styles and composite styles](#) in [G-2] [graph twoway scatter](#) for more information.

What are numbered styles?

p_1 – p_{15} are the default styles for marker labels in [twoway](#) graphs that support marker labels, for example, [twoway scatter](#), [twoway dropline](#), and [twoway connected](#). p_1 is used for the first plot, p_2 for the second, and so on.

p_{1box} – p_{15box} are the default styles used for markers showing the outside values on [box charts](#). p_{1box} is used for the outside values on the first set of boxes, p_{2box} for the second set, and so on.

The “look” defined by a numbered style, such as p_1 or p_{3box} —by look we include such things as text color, text size, and position around marker—is determined by the scheme (see [G-4] [Schemes intro](#)) selected.

Numbered styles provide default looks that can be controlled by a scheme. They can also be useful when you wish to make, say, the second set of labels on a graph look like the first. See [Specifying a markerlabelstyle can be convenient](#) above for an example.

Also see

[G-3] [marker_label_options](#) — Options for specifying marker labels

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).