

usubinstr() — Replace Unicode substring

Description
Diagnostics

Syntax
Also see

Remarks and examples

Conformability

Description

`usubinstr(s, old, new, cnt)` replaces the first *cnt* occurrences of the Unicode string *old* with the Unicode string *new* in *s*. If *cnt* is *missing*, all occurrences are replaced.

When arguments are not scalar, this function returns element-by-element results.

Syntax

string matrix `usubinstr(string matrix s, string matrix old, string matrix new, real matrix cnt)`

Remarks and examples

stata.com

An invalid UTF-8 sequence in *s*, *old*, or *new* is replaced with the Unicode replacement character `\ufffd` before replacement is performed.

Use `subinstr()` if your string does not contain Unicode characters or if you want to replace the substring based on bytes.

Conformability

`usubinstr(s, old, new, cnt):`

s: $r \times c$
old: $r \times c$ or 1×1
new: $r \times c$ or 1×1
cnt: $r \times c$ or 1×1
result: $r \times c$

Diagnostics

`usubinstr(s, old, new, cnt)` returns an empty string if an error occurs.

Also see

[M-5] **subinstr()** — Substitute text

[M-5] **substr()** — Extract substring

[M-5] **_substr()** — Substitute into string

[M-5] **usubstr()** — Extract Unicode substring

[M-5] **_usubstr()** — Substitute into Unicode string

[M-4] **String** — String manipulation functions

[U] **12.4.2 Handling Unicode strings**

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).